

GRAFFITI REMOVER

Safety Data Sheet

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: **GRAFFITI REMOVER**

Synonyms
Graffiti Remover

Product Code
416

Recommended use: Effective cleaner for removing texta colouring and paint from hard surfaces.

Supplier Name CLEAN PLUS CHEMICALS PTY LTD
Address 16 George Young Street AUBURN NSW 2144
Telephone 02 9738 7444
Fax 02 9644 1777
Emergency 1800 201 700
Email customerservice@cleanplus.com.au
Web Site www.cleanplus.com.au
SDS Date 22 September 2016 Version 1.1

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of Safe Work Australia.



Signal Word
Warning

Hazard Classifications

Flammable Liquids - Category 3
Acute Toxicity - Oral - Category 4
Acute Toxicity - Dermal - Category 4
Acute Toxicity - Inhalation - Category 4
Skin Corrosion/Irritation - Category 2
Serious Eye Damage/Irritation - Category 2A
Sensitisation - Skin - Category 1
Acute Hazard to the Aquatic Environment - Category 1
Chronic Hazard to the Aquatic Environment - Category 1

Hazard Statements

H226 Flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H410 Very toxic to aquatic life with long lasting effects.

Prevention Precautionary Statements

P102 Keep out of reach of children.

GRAFFITI REMOVER

Safety Data Sheet

P103	Read label before use.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist, vapours or spray.
P264	Wash hands, face and all exposed skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing, gloves, eye/face protection and suitable respirator.

Response Precautionary Statements

P101	If medical advice is needed, have product container or label at hand.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P330	Rinse mouth.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P363	Wash contaminated clothing before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTRE or doctor/physician if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use alcohol resistant foam, dry agents for extinction.
P391	Collect spillage.

Storage Precautionary Statement

P403+P235 Store in a well-ventilated place. Keep cool.

Disposal Precautionary Statement

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Poison Schedule: S6. Poison

DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
D-limonene	5989-27-5	30 - 60 %
2-Butoxyethanol	111-76-2	30 - 60 %
Ingredients determined to be non-hazardous		Balance
		100%

GRAFFITI REMOVER

Safety Data Sheet

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin Contact: Effects may be delayed. If skin or hair contact occurs, immediately remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre or a Doctor; or for 15 minutes and transport to Doctor or Hospital. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. A component of the material, can be absorbed through the skin with resultant toxic effects. Seek medical advice.

Eye contact: If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

Ingestion: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Immediately call Poisons Centre or Doctor.

Notes to physician: Treat symptomatically. Effects may be delayed.

5. FIRE FIGHTING MEASURES

Hazchem Code: •3Y

Suitable extinguishing media: If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

Specific hazards: Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

Fire fighting further advice: Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

GRAFFITI REMOVER

Safety Data Sheet

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Dangerous Goods – Initial Emergency Response Guide No: 14

7. HANDLING AND STORAGE

Handling: Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and/or the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and must be stored in accordance with the relevant regulations.

This material is a Scheduled Poison Schedule 6 (Poison) and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m ³	ppm	mg/m ³	
2-Butoxyethanol 111-76-2	20	96.9	50	242	Sk

As published by Safe Work Australia.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice - absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as

GRAFFITI REMOVER

Safety Data Sheet

fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: SAFETY SHOES, OVERALLS, GLOVES, CHEMICAL GOGGLES, RESPIRATOR.

MANUFACTURING, PACKAGING AND TRANSPORT: Wear safety shoes, overalls, gloves, chemical goggles, respirator. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

RECOMMENDATIONS FOR CONSUMER USE: Wear safety glasses and gloves. Avoid inhaling vapour. Wash hands after use.

Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Base Units: Litres
Form: Clear Liquid
Colour: Colourless
Odour: Citrus

Solubility: Miscible with water.
Specific Gravity (20 °C): 0.88 - 0.90
Relative Vapour Density (air=1): >1
Vapour Pressure (20 °C): N Av
Flash Point (°C): >50
Flammability Limits (%): N Av
Autoignition Temperature (°C): N Av
Melting Point/Range (°C): N Av
Boiling Point/Range (°C): 170
Decomposition Point (°C): N Av
pH: 7.0 - 8.0
Viscosity: N Av
Total VOC (g/Litre): N Av

(Typical values only - consult specification sheet)
N Av = Not available, N App = Not applicable

GRAFFITI REMOVER

Safety Data Sheet

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents.

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Harmful if inhaled. Material may be an irritant to mucous membranes and respiratory tract.

Skin contact: Harmful in contact with skin. A component can be absorbed through the skin with resultant toxic effects. Contact with skin will result in irritation. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Ingestion: Harmful if swallowed. Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

Acute toxicity

Inhalation: This material has been classified as a Category 4 Hazard.
Acute toxicity estimate (based on ingredients): 10 - 20 mg/L

Skin contact: This material has been classified as a Category 4 Hazard.
Acute toxicity estimate (based on ingredients): 1,000 - 2,000 mg/Kg

Ingestion: This material has been classified as a Category 4 Hazard.
Acute toxicity estimate (based on ingredients): 300 - 2,000 mg/Kg

Corrosion/Irritancy: Eye: this material has been classified as a Category 2A Hazard (reversible effects to eyes).
Skin: this material has been classified as a Category 2 Hazard (reversible effects to skin).

Sensitisation: Inhalation: this material has been classified as not a respiratory sensitiser.
Skin: this material has been classified as a Category 1 Hazard (skin sensitiser).

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

Chronic Toxicity

Mutagenicity: This material has been classified as non-hazardous.

GRAFFITI REMOVER

Safety Data Sheet

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation): This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as a Category Acute 1 Hazard.
Acute toxicity estimate (based on ingredients): <1 mg/L

For the constituent

D-LIMONENE:

48hr EC50 (Daphnia magna): 0.421 mg/L

96hr EC50 (fathead minnow): 0.702 mg/L

Long-term aquatic hazard: This material has been classified as a Category Chronic 1 Hazard. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): <1 mg/L, where the substance is not rapidly degradable and/or BCF \geq 500 and/or log $K_{ow} \geq$ 4.

Ecotoxicity: No information available.

Persistence and degradability: D-Limonene is rapidly degradable.

Bioaccumulative potential: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 1993
Dangerous Goods Class: 3
Packing Group: III
Hazchem Code: •3Y
Emergency Response Guide No: 14

GRAFFITI REMOVER

Safety Data Sheet

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (CONTAINS D LIMONENE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea. This material is classified as a Marine Pollutant (P) according to the International Maritime Dangerous Goods Code.



UN No: 1993
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (CONTAINS D LIMONENE)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1993
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (CONTAINS D LIMONENE)

15. REGULATORY INFORMATION

HSNO Group Standard: HSR002528 - Cleaning Products (Flammable) Group Standard 2006

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)
The Stockholm Convention (Persistent Organic Pollutants)
The Rotterdam Convention (Prior Informed Consent)
Basel Convention (Hazardous Waste)
International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

- The *Standard for the Uniform Scheduling of Medicines and Poisons* (SUSMP) established under the Therapeutic Goods Act (Commonwealth).
- All the constituents of this material are listed on the *Australian Inventory of Chemical Substances* (AICS).

GRAFFITI REMOVER

Safety Data Sheet

16. OTHER INFORMATION

Literary reference

This Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of Clean Plus Chemicals Pty Ltd.

Reason for issue: First issue

Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This SDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Clean Plus Chemicals Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this SDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.